



Scan with your smart phone to view a video on this product.

FLEXSTOR[®] VAC ATTACH

SPECIFICATIONS

- Versatile enough to connect along side the grain vac or directly behind it.
- Hydraulic powered gathering augers & bag winders are used to move all the grain to a central suction inlet inside the bag that is connected to the grain vac via flexible suction tubing.
- As the Vac Attach moves rearward into the grain bag, the grain vac is pulled forward as needed by the tractor powering it to stay in close proximity.
- Height control, counterbalance and hydraulic power is provided by connection to a smaller tractor, acting as a prime mover for the FlexStor Vac Attach.
- Use of a suitable length suction tube between the two pieces of equipment allows the operator to only move the grain vac forward when changing trucks.
- The tractor 3 point hitch allows the operator to raise and lower the gathering augers for transport or positioning inside the bag. A towbar hitch can also be used when a 3 point hitch is not available.
- The bag is wound onto steel tubular cores that can easily be removed by one person.

For More Information:
Koyker Manufacturing
Toll Free: (800) 456-1107
Local: (605) 647-2811
E-Mail: info@koykermfg.com
Website: www.flexstorequipment.com



Manufactured In: Lennox, SD; USA



FEATURES Of Vac Attach

- ✓ Simplifies the labor required when emptying a grain storage bag.
- ✓ The tractor steers the gathering augers to keep them centered inside the bag.
- ✓ Its inherent weight acts as a counterbalance for lifting/winding bag.
- ✓ Manufactured In The USA!

Patent Pending

